



## Pigment Rubine Toner

### General Description :

Pigment Rubine Toner is a rosinated type deep bluish tone with high transparency & high tinctorial strength with moderate light fastness & poor weather fastness. It has versatile use in those printing inks where demands on fastness properties are not too high. It also recommended for low cost air drying paint system.

### PHYSICAL PROPERTIES :

Specific Gravity at 20°C	:	1.550
Sieve Residue	:	0.5 % max
Heat Stability	:	200 °C
Moisture Content	:	1.0 % max
PH of Water Extract	:	7.0
Oil Absorption	:	60-70 CC
Water Soluble	:	3% Max

### FASTNESS CHARACTERISTICS :

Water	: 4-5	Toludine	: 3	Butyl Acetate	: 3
Ethanol	: 2-3	Mineral Turpentine Oil	: 3	Soap	: 2
Butanol	: 2-3	Methyl Ethyl Ketone	: 2-3	Acid	: 3
Acetone	: 3	Linseed Oil	: 4	Alkali	: 3

### LIGHT FASTNESS :

1/1Depth	: 4-5	[16.5%]
1/3 Depth	: 3-4	[8.3%]
1/25 Depth	: 3	[1.6%]

### TECHNICAL RECOMMENDATION : PRINTING INKS PLASTICS OTHER APPLICATIONS

(Letterpress Inks, Air Drying Enamel Paints, Rubber , Offset Inks, N C Lacquer Paints, Leather , PVC , Flexo /Gravure Inks, Plastics.)